

34 Years Serving You!



Introducing the new HDMI podium Speechprompter...



Specifications - SP-15E

Viewable Size - 15 inch

Brightness - 1000 NTS

Signal Input - HDMI, SVGA, NTSC,

Input Voltage - 110 VAC / 12 Volt DC

Resolution - 1024 x 768

Power Consumption - 30-35 Watts

Input Connector - 15-pin D-Type BNC, HDMI

Special Features - Scan-Reverse BNC Loop

Weight - 24lbs



SP-15E

HDMI-NTSC-SVGA Inputs

Give your speaker the ultimate advantage. A true professional tool!

New monitors reverse images internally --no special equipment or software needed!

System includes two housings, monitors, pole, Beamsplitter mirrors and holders

Beamsplitter mirrors are special coated and include radiused corners. Mirror size is 12.75" x 10.0" The top in the industry!

Mirrors are set at the perfect angle and reader height can be adjusted up to 6'6"

Monitors are placed on the floor and are protected by metal housings that "nest together" for easy probability

All metal components with durable powder-coat finish

Extremely tough!

3-year conditional warranty

200 dealers worldwide and ready to serve you!





Phone 920-232-0220

Fax 920-232-1225

Email sales@teleprompters.com

www.teleprompters.com

Contact us today with any additional questions you may have



Made in Oshkosh, Wisconsin - USA